

SPECIFICATION規格／機型		MODEL	JBF 7B2S	JBF 10B2S	JBF 10B2SL	JBF 10B2SXL	JBF 13B2S	JBF 13B2SL	JBF 17B2S	JBF 17B2SL	JBF 19B2S	JBF 19B2SL	JBF 24B2S	JBF 30B2S
FORGING STATION 模數			2											
CUT-OFF DIA. MAX. 最大切斷直徑 (mm)			5	8			10		12		15		18	23
CUT-OFF LENGTH 切斷長度 (mm)			15~55	20~70	28~105	28~120	24~94	30~130	28~105	42~180	35~140	55~185	43~185	63~270
KICK-OUT LENGTH MAX.後托頂出長度 (mm)			45	60	90	115	76	120	90	175	120	180	185	230
PK.O. LENGTH MAX.前托頂出長度 (mm)			10	12	20	22	17	23	20	30	27	30	33	35
CUT-OFF QUILL(DxL)切模 (mm)			20x30	28x46			35x56	38x79	40x66	40x80	46x80	46x80	60x100	75x120
MAIN DIE HOLE(DxL) 母模 (mm)			38x60	50x65	50x105	50x123	60x85	70x135	70x95	80x185	80x123	93x190	100x195	125x240
DIES PITCH母模中心距離 (mm)			48	60			87		93		114		126	138
PUNCH HOLE(DxL)公模束 (mm)			32x60	40x82	40x110	40x110	45x90	45x111	50x103	50x133	60x120	60x170	70x160	90x197
RAM STROKE主滑板行程 (mm)			100	120	150	180	140	200	160	250	200	270	280	360
FORGING POWER壓造力 (ton)			12	25	25	25	40	45	55	55	70	70	130	185
PRODUCTS 產品	SIZE尺寸		3/16(M4)	1/4(M6)			5/16 (M8)		3/8 (M10)		1/2 (M12)		5/8(M16)	3/4(M20)
	MAX.L最長長度 (mm)		40	50	75	100	65	100	75	150	100	150	150	200
	MIN.L最短長度 (mm)		10	12	20	20	14	20	16	30	20	40	25	40
	OPEN UPSET DIA. 母夾最大開啟量 (mm)		Φ12.5	Φ15			Φ20		Φ21		Φ31		Φ32	Φ32
MAX. OUTPUT每分鐘最大產能 (pcs/minute)			300	300	240	210	240	210	210	175	170	135	120	100
MAIN MOTOR主馬達 (hp)			7.5	10	10	10	15	15	15	20	30	30	60	100
APPROX. WT.機械重量 (ton)			3	6	6.8	7.6	8	10	11.5	15	19	22	35	50

DSC01-0526-2017

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)