

JBF SERIES 3-DIE 3-BLOW BOLT FORMER (三模三沖螺絲成型機)



SPECIFICATION規格/機型		MODEL	JBF 7B3S	JBF 10B3S	JBF 10B3SL	JBF 10B3SXL	JBF 13B3S	JBF 13B3SL	JBF 13B3SXL	JBF 17B3S	JBF 17B3SL	JBF 17B3SXL	JBF 17B3SUL
FORGING STATION模數			3										
CUT-OFF DIA. MAX.最大切斷直徑 (mm)		5	8				10			12			
CUT-OFF LENGTH 切斷長度 (mm)		15-55	20-70	24-105	28-125	24-94	30-130	40-180	28-105	42-180	62-230	112-350	
KICK-OUT LENGTH MAX.後托頂出長度 (mm)		45	60	90	115	76	120	175	85	175	225	312	
PK.O. LENGTH MAX. 前托頂出長度 (mm)		10	13	20	22	17	23	30	20	30	36	60	
CUT-OFF QUILL (DxL) 切模 (mm)		20x30	28x46	28x46	28x46	35x56	38x79	38x79	40x66	40x80	40x80	40x80	
MAIN DIE HOLE (DxL) 母模 (mm)		38x60	50x65	50x105	50x123	60x85	70x135	70x185	70x95	80x185	80x240	80x330	
DIES PITCH 母模中心距離 (mm)		48	60				87			93			
PUNCH HOLE (DxL) 公模束 (mm)		32x60	40x82	40x110	40x110	45x90	45x111	45x130	50x103	50x133	50x190	50x200	
RAM STROKE 主滑板行程 (mm)		100	120	150	200	140	200	250	160	250	360	460	
FORGING POWER 壓造力 (ton)		15	28	30	35	50	50	55	70	70	80	80	
PRODUCTS 產品	SIZE 尺寸	3/16(M4)	1/4(M6)				5/16(M8)			3/8 (M10)			
	MAX.L最長長度 (mm)	40	50	75	100	65	100	150	75	150	200	300	
	MIN.L(mm) 最短長度	HEX. 外六角螺絲	10	12	16	20	14	20	30	16	30	50	100
		SOCKET 強力螺絲	12	16	20	25	20	25	40	20	40	50	100
OPEN UPSET DIA. 母夾最大開啟量 (mm)	Φ12.5	Φ15				Φ20			Φ21				
MAX. OUTPUT 每分鐘最大產能 (pcs/minute)		300	300	240	210	240	210	180	210	175	110	80	
MAIN MOTOR 主馬達 (hp)		7.5	10	15	15	15	20	30	20	30	40	40	
APPROX. WT. 機械重量 (ton)		3.5	6.5	7.8	9	10	11.5	14	14	18	21	26.5	

P3-1

DSC02-0526-2017

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)

JBF SERIES 3-DIE 3-BLOW BOLT FORMER (三模三沖螺絲成型機)



SPECIFICATION規格/機型		MODEL	JBF 19B3S	JBF 19B3SL	JBF 19B3SXL	JBF 19B3SUL	JBF 24B3S	JBF 24B3SL	JBF 24B3SXL	JBF 24B3SUL	JBF 30B3S	JBF 30B3SL	JBF 30B3SUL	JBF 33B3S	
FORGING STATION模數			3												
CUT-OFF DIA. MAX.最大切斷直徑 (mm)		15				18				23			26		
CUT-OFF LENGTH 切斷長度 (mm)		35~140	55~185	65~240	115~370	43~185	68~270	78~320	118~370	63~270	83~320	123~370	76~300		
KICK-OUT LENGTH MAX.後托頂出長度 (mm)		120	180	215	325	175	230	280	335	220	285	335	260		
PK.O. LENGTH MAX. 前托頂出長度 (mm)		26	30	35	60	33	36	50	60	35	60	60	45		
CUT-OFF QUILL (DxL) 切模 (mm)		46x80	46x80	60x100	65x100	60x100	60x120	60x120	60x120	75x120	75x120	75x120	84x130		
MAIN DIE HOLE (DxL) 母模 (mm)		80x123	93x190	93x240	93x350	100x195	100x240	100x294	100x360	125x240	125x294	125x370	140x280		
DIES PITCH 母模中心距離 (mm)		114				126				138			156		
PUNCH HOLE (DxL) 公模束 (mm)		60x120	60x170	60x200	60x250	75x160	75x200	75x232	75x232	90x197	90x232	90x240	96x210		
RAM STROKE 主滑板行程 (mm)		200	270	360	500	280	360	420	500	360	430	500	400		
FORGING POWER 壓造力 (ton)		90	90	100	100	160	160	175	175	220	235	250	260		
PRODUCTS 產品	SIZE 尺寸	1/2 (M12)				5/8 (M16)				3/4(M20)			7/8(M22)		
	MAX.L最長長度 (mm)	100	150	200	300	150	200	250	300	200	250	300	225		
	MIN.L(mm) 最短長度	HEX. 外六角螺絲	20	40	50	100	25	50	60	100	40	60	60	50	
		SOCKET 強力螺絲	25	40	50	100	35	50	60	100	60	60	60	60	
OPEN UPSET DIA. 母夾最大開啟量 (mm)	Φ 31				Φ32				Φ32			--			
MAX. OUTPUT 每分鐘最大產能 (pcs/minute)		170	135	110	80	120	100	85	80	100	80	75	75		
MAIN MOTOR 主馬達 (hp)		40	50	50	50	75	75	100	100	100	100	100	125		
APPROX. WT. 機械重量 (ton)		22	25	29	36	40	44	49	54	57	63	69	75		

P3-2

DSC02-0526-2017

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)

JBF SERIES 3-DIE 3-BLOW BOLT FORMER (三模三沖螺絲成型機)

SPECIFICATION規格/機型		MODEL	JBF 36B3SS	JBF 36B3S	JBF 41B3S	JBF 45B3S								
FORGING STATION模數			3											
CUT-OFF DIA. MAX.最大切斷直徑		(mm)	29		34	38								
CUT-OFF LENGTH 切斷長度		(mm)	69~220	89~320	114~400	138~450								
KICK-OUT LENGTH MAX.後托頂出長度		(mm)	185	290	340	390								
P.K.O. LENGTH MAX. 前托頂出長度		(mm)	30	60	60	70								
CUT-OFF QUILL (DxL) 切模		(mm)	90x140	90x140	110x140	115x140								
MAIN DIE HOLE (DxL) 母模		(mm)	160x210	160x294	178x385	195x420								
DIES PITCH 母模中心距離		(mm)	174		195	210								
PUNCH HOLE (DxL) 公模束		(mm)	105x180	105x232	120x250	135x280								
RAM STROKE 主滑板行程		(mm)	300	440	500	580								
FORGING POWER 壓造力		(ton)	320	320	450	600								
PRODUCTS 產品	SIZE 尺寸		1(M24)		1&1/8 (M27)	1&1/4 (M30)								
	MAX.L最長長度		(mm)	150	250	300	355							
	MIN.L(mm) 最短長度	HEX. 外六角螺絲		40	60	80	100							
		SOCKET 強力螺絲		50	60	80	100							
OPEN UPSET DIA. 母夾最大開啟量		(mm)	Φ58		--	Φ62								
MAX. OUTPUT 每分鐘最大產能		(pcs/minute)	85	70	55	45								
MAIN MOTOR 主馬達		(hp)	125	125	150	175								
APPROX. WT. 機械重量		(ton)	78	92	134	167								

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)