

JBF SERIES 4-DIE 4-BLOW BOLT FORMER(四模四沖螺絲成型機)



SPECIFICATION 規格 / 機型		MODEL	JBF 5B4S	JBF 7B4S	JBF 7B4SXL	JBF 10B4S	JBF 10B4SL	JBF 13B4S	JBF 13B4SL	JBF 13B4SXL	JBF 13B4SUL	JBF 17B4S	JBF 17B4SL	JBF 17B4SXL	JBF 17B4SUL	JBF 19B4S	JBF 19B4SL	JBF 19B4SXL	JBF 19B4SLL	JBF 19B4SUL	JBF 19B4SUUL	
FORGING STATION 模數			4																			
CUT-OFF DIA. MAX 最大切斷直徑 (mm)			3	5		8		10			12			15								
CUT-OFF LENGTH 切斷長度 (mm)			11~35	15~55	17~80	20~70	24~105	26~105	30~130	40~180	50~220	28~135	42~180	62~230	112~350	35~140	55~185	65~240	65~310	115~370	115~470	
KICK-OUT LENGTH MAX 後托頂出長度 (mm)			32	45	75	60	90	90	120	175	215	115	175	225	312	120	180	215	270	325	430	
P.K.O. LENGTH MAX 前托頂出長度 (mm)			8	10	17	13	20	20	23	30	34	20	30	36	60	26	30	35	60	60	70	
CUT-OFF QUILL (DxL) 切模 (mm)			18x25	20x30	20x50	28x46	28x46	35x56	38x79	38x79	38x79	40x66	40x80	40x80	40x80	46x80	46x80	60x100	60x100	65x100	60x100	
MAIN DIE HOLE (DxL) 母模 (mm)			28x45	38x60	38x85	50x65	50x105	60x105	70x135	70x185	70x240	70x135	80x185	80x240	80x330	80x123	93x190	93x240	93x294	93x350	93x450	
DIES PITCH 母模中心距離 (mm)			36	48		60		87			93			114								
PUNCH HOLE (DxL) 公模束 (mm)			24x45	32x60	32x90	40x82	40x110	45x110	45x111	45x130	45x175	50x111	50x133	50x190	50x200	60x120	60x170	60x200	60x232	60x250	60x270	
RAM STROKE 主滑板行程 (mm)			80	100	140	120	150	150	200	250	350	180	250	360	460	200	270	360	420	500	610	
FORGING POWER 壓造力 (ton)			10	20	25	40	40	65	65	70	70	85	85	90	90	120	120	130	130	130	145	
PRODUCTS 產品	SIZE 尺寸		1/8(M3)	3/16 (M4)		1/4 (M6)		5/16 (M8)			3/8 (M10)			1/2 (M12)								
	MAX.L 最長長度 (mm)		25	40	65	50	75	75	100	150	200	100	150	200	300	100	150	200	250	300	406	
	MIN.L(mm) 最短長度	HEX. 外六角螺絲		8	10	12	12	16	16	20	30	40	16	30	50	100	20	40	50	50	100	100
		SOCKET 強力螺絲		10	12	16	16	20	20	25	40	40	20	40	50	100	25	40	50	50	100	100
	OPEN UPSET DIA. 母夾最大開啟量 (mm)		--	Φ12.5		Φ15		Φ20			Φ21			Φ31								
MAX.OUTPUT 每分鐘最大產能 (pcs/minute)			250	300	250	300	240	240	210	180	140	200	175	110	80	170	135	110	90	80	50	
MAIN MOTOR 主馬達 (hp)			5	10	15	15	15	20	30	30	30	30	40	40	40	50	50	50	50	50	50	
APPROX. WT. 機械重量 (ton)			3	4.3	6	7.5	9	12.5	14	16.5	20	17	21	24	30	25	29	32.5	36	40	47	

P2-1

DSC03-0526-2017

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)

JBF SERIES 4-DIE 4-BLOW BOLT FORMER(四模四沖螺絲成型機)



SPECIFICATION 規格 / 機型		MODEL	JBF 24B4S	JBF 24B4SL	JBF 24B4SXL	JBF 24B4SUL	JBF 24B4SULL	JBF 30B4S	JBF 30B4SL	JBF 30B4SUL	JBF 30B4SULL	JBF 33B4S	JBF 36B4SS	JBF 36B4S	JBF 36B4SL	JBF 36B4SXL	JBF 41B4S	JBF 45B4S	JBF 50B4S
FORGING STATION 模數			4																
CUT-OFF DIA. MAX 最大切斷直徑 (mm)			18					23				26	29				34	38	42
CUT-OFF LENGTH 切斷長度 (mm)			43~185	68~270	78~320	118~370	118~420	63~270	83~320	123~370	123~425	76~300	69~220	89~320	129~370	129~460	134~400	138~450	152~480
KICK-OUT LENGTH MAX 後托頂出長度 (mm)			175	230	280	335	380	220	285	335	380	260	185	290	340	410	340	390	415
P.K.O. LENGTH MAX 前托頂出長度 (mm)			33	36	50	60	70	35	60	60	70	45	30	60	60	60	60	70	75
CUT-OFF QUILL (DxL) 切模 (mm)			60x100	60x120	60x120	60x120	60x120	75x 120				84x130	90x 140				110x140	115x140	132x155
MAIN DIE HOLE (DxL) 母模 (mm)			100x195	100x240	100x294	100x360	100x420	125x240	125x294	125x370	125x420	145x280	160x210	160x294	160x370	160x450	178x385	195x420	205x450
DIES PITCH 母模中心距離 (mm)			126					138				156	174				195	210	225
PUNCH HOLE (DxL) 公模束 (mm)			75x160	75x200	75x232	75x232	75x272	90x197	90x232	90x240	90x290	96x210	105x180	105x232	105x235	105x270	120x250	135x280	150x305
RAM STROKE 主滑板行程 (mm)			280	360	420	500	580	360	430	500	580	400	300	440	500	600	500	580	620
FORGING POWER 壓造力 (ton)			200	200	215	215	250	265	285	300	320	320	360	380	420	450	520	635	700
PRODUCTS 產品	SIZE 尺寸		5/8 (M16)					3/4 (M20)				7/8 (M22)	1 (M24)				1&1/8 (M27)	1&1/4 (M30)	1&3/8 (M33)
	MAX.L 最長長度 (mm)		150	200	250	300	360	200	250	305	360	225	150	250	300	380	300	355	380
	MIN.L (mm) 最短長度	HEX. 外六角螺絲	25	50	60	100	100	40	60	100	100	50	40	60	100	100	100	100	110
		SOCKET 強力螺絲	35	50	60	100	100	60	60	100	100	60	50	60	100	100	100	100	110
OPEN UPSET DIA. 母夾最大開啟量 (mm)		Φ32					Φ32				--	Φ58				--	Φ62	--	
MAX.OUTPUT 每分鐘最大產能 (pcs/minute)			120	100	85	80	65	100	80	75	60	75	80	70	60	55	50	45	40
MAIN MOTOR 主馬達 (hp)			75	75	100	100	100	100	125	125	125	125	125	125	150	150	175	200	200
APPROX. WT. 機械重量 (ton)			46	51	56	62	68	67	73	79	88	85	92	109	120	135	150	190	230

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)