

JBF SERIES 5&6 MULTIPLE STATION BOLT FORMER (五&六模多沖螺絲成型機)



SPECIFICATION 規格 / 機型	MODEL	JBF 7B5S	JBF 10B5S	JBF 10B5SL	JBF 13B5S	JBF 13B5SL	JBF 13B5SXL	JBF 13B5SUL	JBF 17B5S	JBF 17B5SL	JBF 17B5SXL	JBF 17B6SL	JBF 19B5S	JBF 19B5SL	JBF 19B5SXL	JBF 19B5SLL	JBF 19B5SUL	JBF 19B6SL	JBF 19B6SXL	
FORGING STATION 模數		5	5	5	5	5	5	5	5	5	5	6	5	5	5	5	5	6	6	
CUT-OFF DIA. MAX. 最大切斷直徑 (mm)		5	8		10				12				15							
CUT-OFF LENGTH 切斷長度 (mm)		15~55	20~70	24~105	26~105	30~130	40~180	50~220	28~135	42~180	62~230	42~180	40~140	55~185	65~240	65~310	115~370	55~185	65~240	
KICK-OUT LENGTH MAX. 後托頂出長度 (mm)		45	60	90	90	120	175	215	115	175	225	175	120	180	225	270	325	180	225	
P.K.O. LENGTH MAX. 前托頂出長度 (mm)		10	13	20	20	23	30	34	20	30	36	30	26	30	35	60	60	30	35	
CUT-OFF QUILL (DxL) 切模 (mm)		20x30	28x46	28x46	35x56	38x79	38x79	38x79	40x66	40x80	40x80	40x80	46x80	46x80	60x100	60x100	65x100	46x80	60x100	
MAIN DIE HOLE (DxL) 母模 (mm)		38x60	50x65	50x105	60x105	70x135	70x185	70x240	70x135	80x185	80x240	80x185	80x123	93x190	93x240	93x294	93x350	93x190	93x240	
DIES PITCH 母模中心距離 (mm)		48	60		87				93				114							
PUNCH HOLE (DxL) 公模束 (mm)		32x60	40x82	40x110	45x110	45x111	45x130	45x175	50x111	50x133	50x190	50x133	60x120	60x170	60x200	60x232	60x250	60x170	60x200	
RAM STROKE 主滑板行程 (mm)		100	120	150	150	200	250	350	180	250	360	250	200	270	360	420	500	270	360	
FORGING POWER 壓造力 (ton)		25	45	50	80	85	90	90	105	105	110	125	145	160	170	170	175	195	195	
PRODUCTS 產品	SIZE 尺寸	3/16 (M4)	1/4 (M6)		5/16 (M8)				3/8 (M10)				1/2 (M12)							
	MAX.L 最長長度 (mm)	40	50	75	75	100	150	200	100	150	200	150	100	150	200	250	300	150	200	
	MIN.L 最短長度	HEX. 外六角螺絲	10	12	16	16	20	30	40	16	30	50	30	20	40	50	50	100	40	50
		SOCKET 強力螺絲	12	16	20	20	25	40	40	20	40	50	40	25	40	50	50	100	40	50
OPEN UPSET DIA. 母夾最大開啟量 (mm)	Φ14	Φ15		Φ20				Φ21				Φ31								
MAX. OUTPUT 每分鐘最大產能 (pcs/minute)		240	240	200	200	180	160	120	180	150	120	150	150	135	110	90	70	135	100	
MAIN MOTOR 主馬達 (hp)		10	15	20	30	30	40	40	40	40	40	50	50	50	75	75	75	50	75	
APPROX. WT. 機械重量 (ton)		5.3	9	11	14.5	17	20	24	20	24	27	27	28	33	38	43	48	37	44	

P2-1

DSC04-0526-2017

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE (本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE. (設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)

JBF SERIES 5&6 MULTIPLE STATION BOLT FORMER (五&六模多沖螺絲成型機)



SPECIFICATION 規格 / 機型	MODEL	JBF 24B5S	JBF 24B5SL	JBF 24B5SXL	JBF 24B5SUL	JBF 24B5SULL	JBF 30B5S	JBF 30B5SL	JBF 30B5SUL	JBF 33B5S	JBF 36B5SS	JBF 36B5S	JBF 36B5SL	JBF 41B5S	JBF 45B5S	
FORGING STATION 模數		5	5	5	5	5	5	5	5	5	5	5	5	5	5	
CUT-OFF DIA. MAX. 最大切斷直徑 (mm)		18					23			26	29			34	38	
CUT-OFF LENGTH 切斷長度 (mm)		43~185	58~270	83~320	118~370	118~420	63~270	83~320	123~370	76~300	69~220	89~320	129~370	134~400	138~450	
KICK-OUT LENGTH MAX. 後托頂出長度 (mm)		175	230	280	335	380	220	285	335	260	185	290	340	340	390	
P.K.O. LENGTH MAX. 前托頂出長度 (mm)		33	36	60	60	70	35	60	60	45	30	60	60	60	70	
CUT-OFF QUILL (DxL) 切模 (mm)		60x100	60x120	60x120	60x120	60x120	75x120			84x130	90x120	90x140	90x140	110x140	115x140	
MAIN DIE HOLE (DxL) 母模 (mm)		100x195	100x240	100x294	100x360	100x420	125x240	125x294	125x370	145x280	160x210	160x294	160x370	178x385	195x420	
DIES PITCH 母模中心距離 (mm)		126					138			156	174			195	210	
PUNCH HOLE (DxL) 公模束 (mm)		75x160	75x200	75x232	75x232	75x272	90x197	90x232	90x240	96x210	105x180	105x232	105x235	120x250	135x280	
RAM STROKE 主滑板行程 (mm)		280	360	420	500	580	360	430	500	400	300	440	500	500	580	
FORGING POWER 壓造力 (ton)		230	230	250	250	285	320	340	360	350	400	440	480	630	700	
PRODUCTS 產品	SIZE 尺寸	5/8 (M16)					3/4(M20)			7/8(M22)	1(M24)			1&1/8 (M27)	1&1/4 (M30)	
	MAX.L 最長長度 (mm)	150	200	250	300	360	200	250	305	225	150	250	300	300	355	
	MIN.L 最短長度	HEX. 外六角螺絲	25	50	60	100	100	40	60	100	50	40	60	100	100	100
		SOCKET 強力螺絲	35	50	60	100	100	60	60	100	60	50	60	100	100	100
	OPEN UPSET DIA. 母夾最大開啟量 (mm)	Φ32					Φ32			--	Φ58			--	Φ62	
MAX. OUTPUT 每分鐘最大產能 (pcs/minute)		110	100	90	75	65	90	80	70	75	80	70	60	50	45	
MAIN MOTOR 主馬達 (hp)		100	100	100	100	125	125	125	125	125	125	175	175	200	200	
APPROX. WT. 機械重量 (ton)		53	58	63	69	79	77	84	91	97	106	124	138	168	215	

P2-2

DSC04-0526-2017

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE (本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE. (設備產能依產品之形狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)