

SPECIFICATION 規格/機型		MODEL	JNF 8B5SL	JNF 8B6SL	JNF 10B5SL	JNF 10B6SL	JNF 13B5SL	JNF 13B6SL	JNF 14B5SL	JNF 14B6SL	JNF 17B5SL	JNF 17B6SL	JNF 19B5SL	JNF 19B6SL	JNF 24B5SL	JNF 24B6SL	JNF 24B6SXL
FORGING STATION 模數			5	6	5	6	5	6	5	6	5	6	5	6	5	6	6
CUT-OFF DIA. MAX. 最大切斷直徑 (mm)			8		10		13		14		17		19		24		
CUT-OFF LENGTH MAX. 最大切斷長度 (mm)			23		25		33		33		35		38		45	45	60
KICK-OUT LENGTH MAX. 後托頂出長度 (mm)			25		30		35		40		40		45		55	55	80
CUT-OFF QUILL (DxL) 切模 (mm)			37x 45		45x 55		55x 65		62x 75		72x 80		80x 90		100x110		
MAIN DIE HOLE (DxL) 母模 (mm)			37x 55		45x 66		55x 80		62x 90		72x 95		80x 110		100x135	100x135	100x180
DIES PITCH 母模中心距離 (mm)			37		45		55		62		72		80		100		
PUNCH HOLE (DxL) 公模束 (mm)			25x 58		30x 83		37x 87		42x 100		42x 105		48x 110		60x135		
RAM STROKE 主滑板行程 (mm)			80		95		110		120		120		130		190	190	270
FORGING POWER 壓造力 (ton)			30	35	45	50	80	90	90	100	120	130	150	170	245	260	280
PRODUCT 產品	SOCKET WRENCH 板手套筒 (mm)		ψ 8x 16		ψ 10x 20		ψ 12x 25		ψ 14x 28		ψ 17x 28		ψ 18x 35		ψ 24x45	ψ 24x45	ψ 24x70
	SOCKET SET SCREW 止付螺絲 (mm)		M8x 25		M10x 30		M12x 35		M14x 35		M16x 40		M18x 40		M24x50	M24x50	M24x70
MAX. OUTPUT 每分鐘最大產能 (pcs/minute)			290	270	270	250	225	210	210	200	190	180	170	160	140	130	115
MAIN MOTOR 主馬達 (hp)			10	15	15	20	20	25	30	30	30	40	40	40	50	75	75
APPROX. WT. 機械重量 (ton)			4.6	5.5	6	7	8	9.2	9.5	11.5	12	15	18.5	21	29	33	38

P2-1

DSC07-1223-2016

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)

SPECIFICATION 規格/機型		MODEL	JNF 28B5SL	JNF 28B6SL	JNF 32B5SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL	JNF 32B6SL
FORGING STATION 模數			5	6	5	6	6	5	6	5	6	5	6	5	6	
CUT-OFF DIA. MAX. 最大切斷直徑 (mm)			28		32			36		38		41		45		
CUT-OFF LENGTH MAX. 最大切斷長度 (mm)			48		50	50	80	60		70		80		90		
KICK-OUT LENGTH MAX. 後托頂出長度 (mm)			60		65	65	90	75		95		105		125		
CUT-OFF QUILL (DxL) 切模 (mm)			120x 130		140x150			160x 165		165x 175		180x 180		195x 195		
MAIN DIE HOLE (DxL) 母模 (mm)			120x 140		140x155	140x155	140x260	160x 200		165x 260		180x 285		195x 345		
DIES PITCH 母模中心距離 (mm)			120		140			160		165		180		195		
PUNCH HOLE (DxL) 公模束 (mm)			72x 160		84x180			96x 210		102x 250		108x 250		120x 250		
RAM STROKE 主滑板行程 (mm)			210		230	230	300	250		280		300		340		
FORGING POWER 壓造力 (ton)			330	350	440	460	480	550	600	650	700	780	800	850	920	
PRODUCT 產品	SOCKET WRENCH 板手套筒 (mm)		ψ 28x 50		ψ 32x56	ψ 32x56	ψ 32x85	ψ 36x 70		ψ 38x 90		ψ 42x90	ψ 42x100	ψ 46x 120		
	SOCKET SET SCREW 止付螺絲 (mm)		M27x 55		M32x60	M32x60	M32x85									
MAX. OUTPUT 每分鐘最大產能 (pcs/minute)			125	115	90	85	70	75	70	70	65	65	60	55	50	
MAIN MOTOR 主馬達 (hp)			75	100	100	100	125	125	150	150	150	200	200	250	300	
APPROX. WT. 機械重量 (ton)			42	47	61	69	75	80	89	102	112	114	125	133	148	

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)