

JNFRL SERIES 6 STATION LONG STROKE NUT FORMER (六模長衝程螺帽成型機)



SPECIFICATION規格／機型	MODEL	JNFR 8B6SL	JNFR 10B6SL	JNFR 14B6SL	JNFR 17B6SL	JNFR 19B6SL	JNFR 24B6SL	JNFR 28B6SL	JNFR 32B6SL	JNFR 32B6SXL	JNFR 36B6SL	JNFR 38B6SL	JNFR 41B6SL	
FORGING STATION模數		6												
CUT-OFF DIA. MAX. 最大切斷直徑 (mm)		8	10	14	17	19	24	28	32	32	36	38	41	
CUT-OFF LENGTH MAX. 最大切斷長度 (mm)		20	25	30	35	40	50	55	65	80	70	75	80	
KICK-OUT LENGTH MAX. 後托頂出長度 (mm)		30	38	42	50	58	66	75	85	100	95	100	115	
P.K.O. LENGTH MAX. 前托頂出長度 (mm)		8	10	13	14	17	22	26	32	38	38	38	40	
CUT-OFF QUILL(DxL) 切模 (mm)		28x35	38x45	45x60	55x68	65x75	85x90	94x100	105x120	105x120	115x135	115x135	132x155	
MAIN DIE HOLE(DxL) 母模 (mm)		37x65	45x80	62x100	72x125	80x140	100x160	120x175	140x190	140x240	160x220	165x250	180x280	
DIES PITCH母模中心距離 (mm)		37	45	62	72	80	100	120	140	140	160	165	180	
PUNCH HOLE(DxL) 公模束 (mm)		25x83	30x89	42x100	42x120	48x135	60x160	72x160	84x180	84x186	96x220	102x250	108x250	
RAM STROKE主滑板行程 (mm)		90	100	120	140	165	200	240	260	300	300	310	320	
FORGING POWER壓造力 (ton)		35	50	100	125	170	260	340	460	480	600	700	800	
PRODUCT SIZE產品規格 (mm)		ψ 8x20	ψ 10x30	ψ 14x35	ψ 17x45	ψ 20x50	ψ 24x55	ψ 28x65	ψ 32x70	φ 32x85	ψ 36x85	ψ 38x90	ψ 42x100	
MAX. OUTPUT每分鐘最大產能 (pcs/minute)		280	265	230	180	160	140	110	80	65	65	55	50	
MAIN MOTOR主馬達 (hp)		15	20	30	40	40	75	75	100	125	150	150	200	
APPROX. WT. 機械重量 (ton)		6.2	8	12.5	18	23.5	36	51	73	78	96	114	135	

DSC12-1223-2016

- WE RESERVE THE RIGHT TO CHANGE THE DESIGNS & SPECIFICATIONS WITHOUT NOTICE(本公司隨時進行研究改進的工作，因此保有隨時更改設計、規格尺寸及機械結構之權利，本目錄僅供參考。)
- PRODUCTION CAPACITY DEPENDS ON APPLICABLE PRODUCTS, MATERIAL, TENSILE STRENGTH OF THE WIRE.(設備產能依產品之型狀、材質及線材抗拉強度而有所差異。)
- THE KICK-OUT STROKE IN BRACKET SHOWS THE MAX. LENGTH OF THE PRODUCT ALLOWED FOR ROTATIONAL TRANSFER. (後托頂出長度括弧內之數據表示壓造過程中翻轉產品的最長長度)